

BATTERY MAINTENANCE & RESTORATIVE ADDITIVE ADDITIF DE RENOVATION & MAINTENANCE DE BATTERIE

- For use on any battery that has removeable cell caps. (See illustration)
- Can be used on wet or liquid gel lead acid batteries.
- Maximizes performance & extends battery's normal life.
- Maximizes internal conductivity.
- Dissolves hard sulfation on lead plates.
- Faster charging, longer lasting.
- For old or new lead acid batteries only.

- A priori prévu sur les batteries ouvertes avec couvercles. (Voir illustration)
- Pour les batteries plomb acide avec électrolyte ou Gel liquide.
- Améliore les performances & Prolonge la vie de la batterie.
- Augmente la conductivité interne.
- Ajouté à l'électrolyte pour dissoudre rapidement l'excès de sulfate de plomb.
- Avec Resurex les charges sont plus rapides & tiennent plus longtemps.
- Utile pour la batterie usagée ou neuve.

NON-FLAMMABLE
CONTAINS NO BATTERY ACID
ISO 14001 STANDARDS
100% BIODEGRADABLE

Manufactured by:
DUO-REGEN® TECHNOLOGIES,
LLC USA


36181 East Lake Road, Ste. 145
Palm Harbor, FL 34685-3142
Tel: 727-491-0133
Fax: 727-234-0945

www.batteryadditive.com



DUO-REGEN®
Canada - USA - patent pending

Resurex®
Battery Additive
Additif de Batterie



**FOR BEST
RESULTS
USE WITH**

**MAXI-Life
Pulse®**



**For registration &
product information,
visit our web site:
www.duoregen.com**

16 Fl. Oz./473 mL.

KEEP OUT OF REACH OF CHILDREN.
TENIR LOIN DE LA PORTEE DES ENFANTS.

DIRECTIONS FOR USE:

1. Shake well before using.
2. Avoid contact with metals and direct sunlight.
3. Wear safety glasses while working around batteries.
4. Check fluid level in each cell.
5. Add to battery according to chart.
6. Charge battery after treatment or continue with normal use. Allow 21 charge/discharge cycles for maximum effect.
7. Wash with soap and water to remove electrolyte.

Usage Chart - Dosage:

Average 12 volt Starting
Motorcycle Battery - **2ml per cell**
Car/Boat Battery - **10ml per cell**
Bus/Truck Battery - **20ml per cell**
Golf Cart Battery - **20ml per cell**
Forklift Battery - **180ml per cell**

For heavily sulfated or deep-cycle batteries a second treatment may be required. Ideal for batteries less than 3 years old.

For future battery maintenance (evaporation) use WaterX Additive. See website for details.

Pour les batteries lourdement sulfatées et les batteries à cycle profond, un deuxième traitement pourrait être nécessaire. Idéal pour les batteries de moins de 3 ans.

Pour la maintenance future (compensation de l'évaporation) l'usage de l'additif WaterX est conseillé - Voir notre site Internet pour plus de détails.

